

Touch Dynamic
Breeze
All-in-One

NOW AVAILABLE IN
CORE 2 DUO



Breeze All-in-One

Highlights

- Rackable Motherboard for Easy Maintenance
- Field Upgradeable Fanless All-in-One
- 15" Resistive Touch Screen
- Vesa Wall Mount with Quick Disconnect Base
- Gigabit Lan

CPU Options

- Celeron M 1 Gig Fanless CPU
- Celeron M 1.5MHz
- Core 2 Duo 1.6MHz

Optional

- MSR and Digital Persona UrU
- 12" Rear LCD
- Wireless LAN 802.11 a/b/g Internal



TOUCH DYNAMIC

IMPROVING TOUCH TECHNOLOGY

Touch Dynamic Breeze All-in-One Data Sheet

CPU	Intel Celeron M ULV 1Ghz Fanless / Celeron M 1.5Ghz	Core 2 Duo 1.66Ghz
Chipset	Intel 852GM + ICH4 FSB 400MHz	Intel 945GME FSB 533/667MHz / ICH7M
System Memory	2 x DDR DIMM socket up to 2GB FSB200 / 266MHz	2 x DDR2 Slot support, up to 4GB
Graphic Memory	Share system memory up to 64MB	Shared System memory 224MB
LCD Panel		
LCD Size	15" TFT	15" TFT LCD
Brightness	250 nits	250 nits
Maximal Resolution	1024 x 768	1024x768
Touch Screen Type	Resistive	Resistive
Tilt Angle	0° - 90°	0° - 90°
Storage		
Hard Drive	1 - 2.5" SATA Hard Drive	1 - 2.5" SATA Hard Drive
Flash Memory	Optional compact flash function board	Optional compact flash function board
Expansion		
Mini-PCI Socket	1	1
External I/O		
USB	4 (USB 2.0)	4 (USB 2.0)
Serial Ports	4 x RJ45 Powered Serial Ports with DB9 Adapters (Com3/4 with 5V / 12V by jumper)	4 x RJ45 Powered Serial Ports with DB9 Adapters (Com3/4 with 5V / 12V by jumper)
Keyboard Port	1 PS2	1 PS2
Parallel	1	1
Network	1 Intel Gigabit LAN	1 Intel Gigabit LAN
2nd VGA	1 DB15	1 DB15
Cash Drawer Port	1 x RJ11 (12V / 19V)	1 x RJ11 (12V/19V)
Line-in	1	1
Line-out	1	1
Peripheral		
MSR	ID Tech MSR	ID Tech MSR
Second Display	optional 12.1" 2nd display	optional 12.1" 2nd display
Customer Display	Flush mount VFD display 2 x 20 characters	Flush mount VFD display 2x20 characters
Wireless LAN	802.11a/b/g mini PCI wireless LAN card (option)	802.11a/b/g mini PCI wireless LAN card (option)
Scanner	Integrated 2D Omni-directional scanner	Integrated 2D Omni-directional scanner
Power Supply	90W, 19V power adapter	90W, 19V power adapter
EMC & Safety	FCC / CE Class A, LVD	FCC, Class A, CE, LVD
Operating Temperature	5°C - 40°C (41°F - 104°F)	5°C - 40°C (41°F - 104°F)
Storage Temperature	-20°C - 55°C (-4°F - 131°F)	-20°C - 55°C (-4°F - 131°F)
Operating Humidity	20% - 80% RH non condensing	20% - 80% RH non condensing
Storage Humidity	20% - 85% RH non condensing	20% - 85% RH non-condensing
Dimension	17.74" x 12.15" x 10"	17.74" x 12.15" x 10"
Weight	15.4 lbs	15.4lbs
OS Support	Windows XP, WEPOS, XP Embedded, WIN 2000 Pro Embedded, Vista Business Pro, Linux	



bolt down stand



rear view w/ customer display



rackable motherboard



integrated scanner