

# QuickScan® QS2500

## Data Sheet

Linear Imager



**Ideal for:**

- Retail applications
- Health care
- Inventory
- Office automation
- Document tracking
- Light industrial

**Features:**

- Aggressive reading and an extended depth-of-field
- Reads Reduced Space Symbology (RSS), PDF417 and linear codes for flexibility
- Ergonomic "aim and shoot" design
- Reliable and durable, providing long lasting performance

**Mechanical**

**Dimensions**  
 Height: 7.3" / 18.5 cm  
 Width: 2.9" / 7.4 cm  
 Length: 4.5" / 11.4 cm  
**Weight:** 6.3 oz. / 179 g (cable not included)

**Environmental**

**Temperature Rating:**  
 Operating: 32° to 113° F / 0° to 45° C  
 Storage: -22° to 149° F / -30° to 65° C  
**Humidity:**  
 Operating: 5 to 95% NC

**Shock:** Withstands ten 5.0' (1.5m) drops to concrete  
**Water & Dust:** Resistant, IEC 60529 rating IP42DW  
**ESD protection:** Functional after 15kV discharge

**Optical**

**Light Source:** 660nm Visible Red Diode  
**Scan Rate:** 200 scans/sec  
**Scan Width:** 4.0"/10.2 cm at 5.0"/12.7 cm from label  
**Resolution:** 5 mils / 0.13mm  
**Print Contrast:** 25% or higher  
**Pitch:** ±60°  
**Skew:** ±75°  
**Scan angle:** 46°

**Ambient Light Immunity**  
 Artificial Light: 6,968 foot candle / 75,000 Lux  
 Sunlight: 6,968 foot candle / 75,000 Lux  
**Depth of Field:** Refer to table below

DEPTH OF FIELD* Range Comparisons	
LABEL DENSITY	RANGE
5 mils	1.0" - 4.5" / 2.5 - 11.4 cm
10 mils	0.05" - 8.5" / 1.3 - 21.6 cm
13 mils (100% UPC)	0.5" - 11" / 1.3 - 28.0 cm
20 mils	1.0" - 16" / 2.5 - 40.6 cm
40 mils	2.0" - 28.0" / 5.0 - 71.0 cm

\* Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

**Electrical**

**Operating Current:**  
 Operating: 225 mA @ 5 VDC  
 Standby: 100 mA @ 5 VDC

**Communications**

- RS-232
- Keyboard Wedge
- Wand Emulation
- USB
- IBM 46XX
- IBM USB

**Decoding Capability** (autodiscriminates)

- UPC A, E / EAN 8, 13 / JAN 8, 13 (Including add-ons P2/P5)
- Code 128
- Pharmacode 39
- Codabar
- Industrial 2 of 5
- RSS-14
- RSS Expanded
- MSI/Plessey
- Telepen
- Code 11
- Code 93
- Code 39
- Interleaved 2 of 5
- Matrix 2 of 5
- RSS-14 Stacked
- RSS Limited
- UK/Plessey
- Code 16K
- PDF417 with audio assist

**Safety & Regulatory**

**Electrical:** Complies to UL and cUL  
**Emissions:** Complies to FCC-A; EN 55022-B; VCCI-A  
**Laser Classification:** IEC 60825 Class 1 LED



**Accessories**



P/N: 7-0803 (Gray);  
 P/N: 7-0832 (Black)  
 Hands Free Stand

P/N: 7-0393  
 Tabletop or  
 Wall Mount

PSC Inc.  
 959 Terry Street  
 Eugene OR 97402-9150 USA  
 Tel: 800 695 5700 or 541 683 5700  
 Fax: 541 345 7140  
[www.psc.com](http://www.psc.com)



Copyright © PSC Inc. 2002-2005. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying or altering of this document is prohibited without express written consent from PSC. PSC, QuickScan and the PSC logo are registered trademarks of PSC Inc. All other brand and product names are trademarks of their respective owners. Additional information concerning this product or other PSC products and services can be found at the PSC web site: [www.psc.com](http://www.psc.com). Product specifications are subject to change without notice.

