

# POS X

POINT OF SALE  
PERFECTED

## XTS4100 SERIES

LCD TOUCH MONITOR

The XTS4100 Series LCD touchscreen monitor has been designed to outperform its competition in both quality and value. With pin-point accuracy, the crisp image and intuitive controls make this a must-have component in any next-generation point-of-sale system. The splash-resistant screen, extra-thick LCD glass and solid bump free operation make the XTS4100 a great choice for Restaurants, Cafes, Autoshops or any location in need of touch functionality in a small space.



### KEY FEATURES

- Dual video inputs come standard (VGA and DVI-I)
- 10" active matrix display
- USB Touch interface maximizes compatibility
- Bump-free 90-degree tilting base
- VESA mountable
- 3 year warranty



LCD TOUCH MONITOR

# XTS4100 Series Specifications

<b>PART NUMBER</b>	XTS4100
<b>PANEL SIZE</b>	10" TFT Active Matrix Display
Display Area	8.3" (w) x 6.24" (H)
Touch Screen	5-Wire Resistive, 2.8mm glass, 35+ millions taps per location
Resolution	SVGA 800 X 600
Touch Active Area	8.2" x 6.14"
<b>DISPLAY</b>	
PC Video Interface	Analog RGB (VGA) & 24 pin DVI-I
Brightness	250 cd/m2
Pixel Pitch	0.264" X 0.264"
Colors	262,144 colors
Contrast Ratio	400 :1
On Screen Control	Auto Configure, Brightness, Contrast, Phase, H-position, V-position, recall
Back Controls	Power on/off with LED, menu, auto tune, adjustment(+/-)
Viewing Angle	160°
Housing	Metal Housing
<b>PHYSICAL</b>	
Dimensions	9.84"(w) x 9.44"(H) x 7.28"(D)
Weight	7.2 lbs
Tilt Angle	0° to 90°
Housing Color	Black
Stand Style	Cable Management Base
Mounting Options	Desktop Placement, VESA 75mm x 75mm
<b>ELECTRICAL</b>	
Adapter Input	100-240 VAC, 50-60Hz
Adapter Output	12 VDC, 3A (C+)
<b>ENVIROMENTAL</b>	
Temperature Operating	32° F to 114° F operating
Temperature Storage	-4° F to 140° F
Humidity	10% - 90% non-condensing
<b>WARRANTY</b>	3 Year Limited
<b>CERTIFICATIONS</b>	FCC, CE, MIC, UL, RoHs
<b>OPERATING SYSTEM</b>	DOS/WIN NT 4/WIN 9X/WIN ME/WIN 2000/WIN CE/XP/VISTA/Linux/Mac

